



Rovatti PTO Pump Cart & 3 Point Frame

2-1-2018



- ◆ Galvanized 3 point frame or 2 wheel cart.
- ◆ Cart comes with clevis style hitch, high quality Irriland 4 lug axles , 8" wheels, and 6.5" x 16" tires.
- ◆ 1-3/8" x 6 spline PTO drive line.
- ◆ Galvanized FPT inlet and outlet fittings.
- ◆ Tuf-Skin Prime pump with 1" ball valve.
- ◆ Tuf-Skin butterfly valve for priming.
- ◆ Tuf-Skin pressure gauge on outlet fitting.

	Fully Fitted	
Rovatti pump	Inlet	Outlet
T2-50-E	4" FPT	3" FPT
T3-80A-E	5" FPT	4" FPT

- ◆ B Type fittings and other adapters for the inlet and outlet are available.
- ◆ Suction lines and supply hoses available.
- ◆ Call us for a quote!

Part #	Description	2/1/2018 Code H List
RV-T2-50-E-FFC	Rovatti PTO pump + fully fitted cart	
RV-T2-50-E-FF3	Rovatti PTO pump + fully fitted 3 point frame	
RV-T3-80A-E-FFC	Rovatti PTO pump + fully fitted cart	
RV-T3-80A-E-FF3	Rovatti PTO pump + fully fitted 3 point frame	

540 RPM	GPM	106	119	132	159	185	211	238	264	330	396	462
T2-50-E	PSI	149	149	149	148	147	146	144	141	125		
	HP	24	25	26	28	30	32	33	35	39		
T3-80A-E	PSI				175	175	175	175	175	174	170	166
	HP				38	40	42	44	46	53	60	66

Pump performance is approximate and can vary depending on elevations, atmospheric conditions, suction lift, and other factors. Universal Sales reserves the right to change product specifications, designs, standard equipment, and pricing without notice. Valves and fittings are rated at 150PSI.