

Read this first!

Before installing pods on to the poly pipe, unroll the poly pipe and hold it down straight with stakes or weights. Leave it held down straight for at least 24 hours to release the coil memory and relax before installing the pods.

Filling or pressurizing the poly pipe with water and leaving it out in the sun will help this process.

1) Uncoil:



2) Hold straight:



3) After at least 24 hours install the pods:



INSTALLING IRRIPOD POD SKIDS

Step 1

The Tow Hook fitting will need to be fitted to the end of the Pod/Sprinkler line that is furthest from the irrigation hydrant, valve, or mainline connection.

Step 2

With the Tow Hook fitting in place, mark a position that is 3' to 6' from the tow fitting. This is where you will install the first Pod Skid.

Step 3



Lay pipe over Skid base and Cross Tee Anchor (check orientation).



Drill 15mm or 9/16" hole and remove all drilling swarf.



Select the saddle to fit your sprinkler, install rubber O-ring on saddle, locate saddle onto pipe and cross tee anchor – ensure fastening nuts are tightened evenly.



Screw sprinkler into sprinkler riser.



Locate body on skid base and push firmly down to engage grip lugs.



Secure top body by screws around the base.



Fix wire clip into opposing holes on body sides.



Screw the wire clip holders into the holes provided.



The pod is now assembled.

Step 4

Having completed the assembly of the first Pod Skid, measure along the pipe 40'-60' (spacing may vary by design). This is where you will place the next Pod Skid. You now need to assemble this Pod (repeat Step 3). Repeat this process until you have assembled all of the Pod Skids for this line.

Step 5

You should now have all the Pod Skids fitted to the Tubing/Sprinkler line and the Tow Hook on the sprinkler end of the line 3' to 6' from the first sprinkler. Now connect an Irripod fitting to the pod line and connect to your hydrant, valve, or water source.

6-1-2013

Disclaimer

While every effort has been made to ensure accuracy, neither Irripod, Universal Sales, nor any employee of these companies, shall be liable on any grounds whatsoever to any party in respect of decisions or actions they may make as a result of using this information. Irripod reserves the right to make changes without notice to any service or product specification to improve reliability, function, or design. Irripod is a registered trademark of Irripod Ltd. © 2006 Irripod Limited. All rights reserved.